

ARMORTECH ULTRA-BOARD TECHNICAL DATA SHEET

Material	Heavy Duty Builder Board
Application	Surface Protection
Available Size	400sf

FEATURES:

- Heavy duty
- Helps prevent damage from jobsite moisture, dirt, minor impacts and scratches and scrapes.
- Recycled, Reusable and Recyclable.
- Moisture resistant.
- Easy to cut.
- Reusable and easily rolls up for quick storage.

INSTRUCTIONS:

Place on desired clean surface and unroll. Cut to length with utility knife or scissors. For larger areas, seam multiple pieces together with tape. Do not adhere tape directly to floors. If needed, apply a light tack painters' tape to the floor (testing that it will not damage the floor) then tape Ultra-Board to the painter's tape. When finished, sweep off dirt and debris, roll up Ultra-Board and reuse.

HANDLING AND STORAGE:

No special handling requirements.
Keep away from flammable and combustible material.

Products will not release hazardous chemicals under normal conditions of use.

INSTALLATION GUIDELINES:

- Clean the surface to be protected before installing Ultra-Board as trapped debris can damage surfaces.
- When more than one length is needed, tape sections together.
- Applied surface must be dry before installation.
- When covering a newly finish coated floor, wait at least 72 hours and follow the finish coat manufacture's guidelines for proper curing and drying times. Test a small area to ensure floor is fully cured.
- Using low tack painter's tape is recommended to tape down the start and end of application to the surface.

