

ARMORTECH VANGUARD TECHNICAL DATA SHEET

Thickness	2mm
Film	Woven fabric wear layer
Underside	2mm foam cushioning
Material Use	Surface Protection
Available Size	39" x 30.77' per roll – 100sf

FEATURES:

- Double layer construction has a 2mm cushion zone shielded in a tough, durable woven fabric.
- Helps prevent damage from jobsite moisture, dirt, minor impacts and scratches and scrapes.
- Attached lip and tape connection system
- Printed gridlines make it extremely easy to install.
- Lightweight.
- Reusable and easily rolls up for quick storage.

INSTRUCTIONS:

Place on desired surface and unroll.
 Cut to length with utility knife. For larger areas, seam multiple pieces together with attached overlap and tape. Use low tack painters' tape (test tape on the surface before use) to affix Vanguard to the surface. When finished, roll up Vanguard and reuse.



HANDLING AND STORAGE:

No special handling requirements.
 Keep away from flammable and combustible material.
 Products will not release hazardous chemicals under normal conditions of use.

INSTALLATION GUIDELINES:

- Clean the surface to be protected before installing Vanguard as trapped debris can damage surfaces.
- When more than one length is needed, use attached overlap and tape adjoin sections together.
- Applied surface must be dry before installation.
- When covering a newly finish coated floor, wait at least 72 hours and follow the finish coat manufacture's guidelines for proper curing and drying times. Test a small area to ensure floor is fully cured.
- It is not recommended to leave heavy objects directly on the material for more than 24 hours.
- Using low tack painter's tape is recommended to tape down the start and end of application to the surface.
- Painter's tape can be used to join sections together.